



Cubicle Curtain Factory, Inc.
7810 S Dixie HWY.
West Palm Beach, FL 33405
800-588-9296
www.CubicleCurtainFactory.com



SECTION 10 21 23 - ARCHITECTURAL SPECIFICATIONS SIMPLY 66® SNAP SYSTEM & TRACK

These specifications are current to meet NFPA701 standards as of January 1, 2023

SECTION 10 21 23 - CUBICLE CURTAIN TRACK SYSTEM AND SIMPLY 66® SNAP CURTAINS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following:
 - 1. Simply 66® snap-cubicle curtain tracks and curtain carriers.
 - 2. Simply 66® snap-cubicle curtains. "Curtains, namely, fabric or plastic curtains comprised of upper and removable lower panels that snap together."
- B. Related Sections include the following:
 - 1. Division 6 Section "Rough Carpentry."
 - 2. Division 9 Section "Gypsum Board Assemblies, Acoustical Panel Ceilings, Acoustical Tile Ceilings."

1.3 PERFORMANCE REQUIREMENTS

- A. Curtains: Provide curtain fabrics with the following characteristics:
 - 1. Fabrics are launderable to a temperature of not more than 140 degrees Fahrenheit.
 - 2. Fabrics are inherently flame resistant and are identical to those that have passed NFPA 701 when tested by a testing and inspecting agency acceptable to authorities having jurisdiction.

- a. Identify curtains with size. Provide tight ceiling-to-floor and tight track length measurements.

1.4 SUBMITTALS

- A. Product Data: Submit copies of manufacturer's detailed technical data for materials, fabrication and installation of Simply 66® snap cubicle curtains "Curtains, namely, fabric or plastic curtains comprised of upper and removable lower panels that snap together" and tracks specified herein. Include catalog cuts of fittings, anchors, fastenings and accessories.
- B. Shop Drawings: Show layout and types of cubicles, sizes of curtains, number of carriers, anchorage details, and conditions requiring accessories. Indicate dimensions taken from field measurements.
- C. Samples for Verification: Full-size units of each type of the following products:
 - 1. Curtain Fabric: 12-inch square swatch or larger Sample as required to show complete pattern repeat, from dye lot used for the Work, with specified treatments applied. Mark top and face of material.
 - 2. Mesh Top: Not less than 4 inches square.
 - 3. Curtain Track: Not less than 4 inches long.
 - 4. Curtain Carrier: Full-size unit.
- D. Cubicle Schedule: Use same room designations as indicated on Drawings.
- E. Product Certificates: Signed by manufacturers of tracks and curtains certifying that products furnished comply with requirements.
- F. Maintenance Data: For tracks and curtains to include in maintenance manuals specified in Division 1.

1.5 PROJECT CONDITIONS

- A. Environmental Limitations: Do not install curtains until spaces are enclosed and weatherproof, wet work in spaces is complete and dry, work above ceilings is complete, and ambient temperature and humidity conditions are maintained at the levels indicated for Project when occupied for its intended use.
- B. Field Measurements: Where curtains are indicated to fit to other construction, verify dimensions of other construction by field measurements before fabrication and indicate measurements on Shop Drawings. Coordinate fabrication schedule with construction progress to avoid delaying the Work.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

A. Manufacturers: Subject to compliance with requirements, provide products by the following:

1. Cubicle Curtain Factory, Inc.
7810 S Dixie Highway
West Palm Beach, Florida 33405
Toll Free: (800) 588-9296
Tel: 561-202-0040
Fax: 866-804-5692

2.2 CURTAIN TRACKS

- A. Extruded-Aluminum Track No. 1200: 1-3/8 inches wide by 3/4 inch high aluminum track.
- B. Extruded-Aluminum Suspended Track No. 1100: 1-7/16 inches wide by 15/16 inch high aluminum track.
1. Curved Track: Factory fabricated 12-inch radius bends.
 2. Finish: White baked enamel.
- C. Track Accessories: Fabricate splices, end caps, connectors, end stops, coupling and joining sleeves, wall flanges, brackets, ceiling clips, and other accessories from same material and with same finish as track.
1. Suspended Track Support: Not less than 1-inch OD aluminum tube.
 2. End Stop: Removable.
- D. No. 12 Curtain Carriers: Two nylon rollers, nylon axle and tangle free nylon swivel stem with nickel-plated steel hook.
- E. No. 11 Curtain Carriers: One-piece nylon glide, tangle free nylon swivel with nickel-plated steel hook.
- F. No. 20 Breakaway Carrier: Three-piece nylon wheels, body and hook (recommended for use in No. 1200 Cubicle Track).
- G. Exposed Fasteners: connector snap-system Nickel Plated Brass / machine set.
- H. Concealed Fasteners: connector snap-system Nickel Plated Brass / machine set.

2.3 CURTAINS

- A. Curtain Fabric: Cubicle manufacturer's standard, as follows:
1. Fiber Content: 100 percent polyester, inherently and permanently flame resistant. Complies with NFPA 701 fire code standards.
 2. Products: Subject to compliance with requirements, provide the following:
 - a. Cubicle Curtain Factory, Inc. / Simply 66® snap-cubicle curtain system "Curtains, namely, fabric or plastic curtains comprised of upper and removable lower panels that snap together."
 - 1) Pattern: As selected by Architect from manufacturer's full range of available fabrics.
 - 2) Color: As selected by Architect from manufacturer's full range of available colors.
- A. Mesh: Double turned with 1 1/4 inch fire retardant reinforced tape sewn into top hem of mesh. White or beige antimicrobial nylon mesh with openings having a minimum of 70 percent open (1/2" diagonal). #2 grommets to be made of nickel-plated brass that are machined and placed six (6") inches on center. Along bottom horizontal width of mesh, a connector snap-system of Nickel Plated Brass / machine set with nickel-plated brass silver cap cover is to be machined in place and set at 4-9/16 inch on center.
- B. Curtain Snaps: At top horizontal width, of 66"W x 66"L panels double-sided connector snap-system made of Nickel Plated Brass and machine set at 4-9/16 inch on center and machined into top header of every curtain panel.

2.4 CURTAIN FABRICATION

- A. Fabricate curtains to comply with the following requirements:
1. **Horizontal Width:** Finished panel width is 66" horizontal. Panel to be manufactured with 1 1/4" double turned, double needle lock-stitch top, side and bottom hems. At top horizontal width, of 66"W x 66"L panels a double-sided connector snap-system made of Nickel Plated Brass and machine set at 4-9/16 inch on center and machined into top header of every curtain panel.

Vertical Length: Finished vertical length is set at only one finished size of 66" so that every manufactured panel will fit every track application using the Simply 66® Snap Panel System "Curtains, namely, fabric or plastic curtains comprised of upper and removable lower panels that snap together" allowing a 10-12" clearance from finished floor, unless otherwise specified.
 2. Mesh: Mesh to be double-turned with reinforced header tape along top hem and stitched with double needle lock stitch no less than 1 1/4 inch in width.
 3. Mesh to be manufactured in one horizontal continuous piece to fit each room track. The continuous mesh is rounded up to the track size in 59" increments.
 4. Finished vertical mesh to be manufactured to fit a specific facility application of track installation so that the finished vertical size of each mesh is equal to ceiling to floor (tight measure) minus 66" panel size and minus 10-12" floor to curtain clearance, unless otherwise specified.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. General: Install tracks level and plumb, according to manufacturer's written instructions. Provide track fabricated from one continuous length up to 18 feet.
 - 1. Curtain Track Mounting. Select One: Surface Suspended Recessed.
- B. Surface Track Mounting: Fasten surface-mounted tracks at intervals of not less than 24 inches. Fasten support at each splice and tangent point of each corner. Center fasteners in track to ensure unencumbered carrier operation. Attach track to ceiling as follows:
 - 1. Mechanically fasten directly to bottom of concrete deck with anchor screws.
 - 2. Mechanically fasten directly to finished ceiling with toggle bolts.
 - 3. Mechanically fasten to furring through suspended ceiling with screw and tube spacer.
 - 4. Mechanically fasten to suspended ceiling grid with screws.
- C. Suspended Track Mounting: Install track with suspended supports at intervals of not more than 84 inches. Fasten support at each splice and tangent point of each corner. Secure ends of track to wall with flanged fittings or brackets.
- D. Track Accessories: Install end caps, connectors, end stops, coupling and joining sleeves, and other accessories as required for a secure and operational installation.
- E. Curtain Carriers: Provide curtain carriers adequate for 6-inch spacing along the full length of the curtain.
- F. Curtains: Snap curtains to curtain mesh. Start from one end of mesh to middle of mesh. Overlap to snap indicated by tags on curtain. For last panel, start snaps from opposite end of mesh and snap to middle to complete installation.

3.2 DEMONSTRATION

- A. Train Owner's maintenance personnel to adjust, operate, and maintain safety- loading units.
 - 1. Train Owner's maintenance personnel on procedures and schedules for changing curtains and maintaining cubicles.

3.3 PROTECTION

- A. Protect installed recessed track openings with non-residue adhesive tape to prevent debris from ceiling finishing operations from impeding carrier operation.

END OF SECTION 10190